

## Premier Darkroom Louver

### Model DV99

For use with Premier Exhaust Fan Models D-68 and DVM-199A.

Exhaust fans work best in a darkroom equipped with fresh air supply louvers or some other kind of air supply. If there is no air supply to the darkroom, the exhaust fan will be working against a vacuum and can do nothing.

**Note:** For maximum exhaust efficiency, it is recommended that an air intake supply vent (like the DV99) be installed in a wall opening opposite the motorized exhaust vent.

The DV99 is a light tight, louvered air vent which permits air to pass through for a slow, but steady, movement of air. Unit is 1½" deep. Fits into an 8" x 8" opening.



EPR654 Darkroom Vent

DV99

## CPM/Delta Electrostatic Air Scrubber™ Portable

Cleans and removes 97% of airborne particles of bacteria, smoke, dust, mold, pollen and other contaminants.

A Protectair prefilter removes larger particles and a permanent UL approved, heavy duty, self-charging electrostatic filter removes particles as small as one micron. A monthly flush with clean water returns filters to like- new condition.

Cleans a 20 ft. x 20 ft. area more than 5 times per hour. 10½" square. Includes carrying handle and 8 ft. heavy duty cord.



ECP310005 Electrostatic Air Scrubber

50110

## CPM/Delta BLACK OUT™ Power Exhaust Fan

Keep your workspace fresh and properly ventilated for safety and comfort.

The fan draws a complete change of air every 3 minutes in a 10' x 10' room.

Oversized fan blades and thermally protected motor are rated at 300 CFM.

Computer designed baffles in 12" x 12" louvers allow air exchange to flow freely and still maintain a totally light-tight environment. For extra protection the interiors of all louvers are fully painted with matte black. Components are UL listed. 6" standard duct.



ECP691 Fan/Louvers-Ductwork

50020

## CPM/Delta Light-tight Louvers

Four light tight louvers complete the ventilation system.

Louvers should be installed in the wall (or door) opposite the fan assembly to provide a light tight air inlet and free air flow through the darkroom.



ECP695 12 x 12 Light-tight louvers

ECP696 12 x 24 Light-tight louvers

ECP311202 12 x 12 Filtered Light-tight louvers

ECP311204 12 x 24 Filtered Light-tight louvers

50070

50040

50050

**PERSONAL SERVICE IS OUR #1 PRIORITY**



East: 111 Asia Place, Carlstadt, NJ 07072

(201) 939-7722

FAX: (201) 939-7782

West: 2710 McCone Ave., Hayward, CA 94545

(510) 293-0575

FAX: (510) 293-0565