

# FUJIFILM

# X-SERIES

# DIGITAL CAMERAS

## X-T1



- 16.3MP APS-C X-Trans CMOS II Sensor
- EXR Processor II
- 0.5" 2,360k-Dot 0.77x OLED Viewfinder
- 3.0" 1,040k-Dot Tilting LCD Monitor
- Full HD 1080p Video Recording at 60 fps
- Built-In Wi-Fi Connectivity
- Weather-Resistant Body Construction
- Continuous Shooting up to 8 fps
- Intelligent Hybrid AF and Focus Peaking
- Includes EF-X8 Shoe-Mount Flash Unit

X16421452 X-T1 Body (Black)  
X16442755 X-T1 Body (Silver)  
X16421555 X-T1 Kit w/XF18-55 Lens

## X-Pro1



- 16.3 MP APS-C X-Trans CMOS Sensor
- FUJIFILM proprietary X-Mount
- 2nd Generation Hybrid Viewfinder
- 3.0" LCD Monitor (1,230,000 dot resolution)
- Focal Plane Shutter
- TTL Flash Sync
- 2 New Film Simulation Modes
- Start-Up time in QuickStart Mode - 0.5 sec.
- JPEG + RAW (Process In-Camera)
- 100-25,600 ISO Capabilities
- HD 1080p Video w/Stereo Sound
- Magnesium Alloy Body
- High Speed Contrast Autofocus
- Exposure Control - TTL 256 Zones

X16225391 X-PRO1 Digital Camera

## X-E2



- 16.3MP APS-C X-Trans CMOS II Sensor w/ EXR Processor II
- Intelligent Hybrid Auto Focus
- Ultra-fast autofocus of 0.08sec.\*
- 2.36 Million dot OLED Viewfinder
- Built-in Diopter Adjustment
- Bright, high contrast 3.0" (1040K dot) LCD
- Digital Split Image manual focus with Focus Peaking
- High speed continuous shooting of 7fps at full resolution (max. 28 frames)
- Start-up time 0.5 sec in Quick Start mode
- Full HD Movie @ 60fps/30fps (1920x1080) w/ Hybrid AF
- One-touch wireless connectivity (IEEE 802.11 b/g/n)
- JPEG + RAW w/ in-camera RAW Converter
- Q (Quick Menu) button
- Microphone outlet

X16404870 X-E2 Black (Body Only)  
X16404791 X-E2 Silver (Body Only)  
X16405018 X-E2 Black Kit w/18-55mm lens  
X16404935 X-E2 Silver Kit w/18-55mm lens

**ARGGRAPH**  
CORP

[www.argraph.com](http://www.argraph.com)

Address: 111 Asia Place, Carlstadt, NJ 07072  
Phone: 201.939.7722

Twitter: @argraph

# FUJIFILM

## X-SERIES DIGITAL CAMERAS

### X-M1



- 16.3 MP APS-C X-Trans CMOS Sensor
- 3.0" Tilting LCD Monitor (920k dot resolution)
- Face Detection
- Focal Plane Shutter
- TTL Flash Sync
- Start-Up time in QuickStart Mode - 0.5 sec.
- 100-25,600 ISO Capabilities
- HD 1080p Video w/Stereo Sound
- WiFi Capability IEEE 802.11 b/g/n
- High Speed Contrast Autofocus
- Exposure Control - TTL 256 Zones
- Battery life 350 shots
- 8 Advanced Filters

|           |                                     |
|-----------|-------------------------------------|
| X16390392 | X-M1 Black (Body Only)              |
| X16390110 | X-M1 Silver (Body Only)             |
| X16391516 | X-M1 Kit w/16-50mm XC Lens (Silver) |
| X16390952 | X-M1 Kit w/16-50mm XC Lens (Black)  |
| X16403149 | X-M1 Kit w/16-50mm XC Lens (Brown)  |

### X-A1



- 16.3 MP APS-C CMOS Sensor
- FUJIFILM proprietary X-Mount
- 3.0" Tilting LCD Monitor (920k dot resolution)
- Face Detection
- Focal Plane Shutter
- TTL Flash Sync
- Start-Up time in QuickStart Mode - 0.5 sec.
- JPEG + RAW (Process In-Camera)
- 100-25,600 ISO Capabilities
- HD 1080p Video w/Stereo Sound
- WiFi Capability IEEE 802.11 b/g/n
- High Speed Contrast Autofocus
- Exposure Control - TTL 256 Zones
- Battery life 350 shots
- 8 Advanced Filters
- Focus Peaking Assist

|           |                                    |
|-----------|------------------------------------|
| X16395586 | X-A1 Kit w/16-50mm XC Lens (Black) |
|-----------|------------------------------------|

### X100S



- 16.3 MP X-Trans APS-C CMOS II Sensor
- EXR Processor II
- Intelligent Hybrid Autofocus (High speed Phase Detection and Contrast AF)
- FUJINON 23mm (35mm Equivalent) Single Focal Length Fixed F2 Lens
- Switchable Optical/Electronic Viewfinder
- 2.8" LCD Monitor w/460k - dot resolution
- JPEG + RAW (Process In-Camera)
- 100-12800 ISO Capabilities
- HD 1080p 60fps/30fps Video w/Stereo Sound
- Classic Design Magnesium Alloy Body
- Q Button
- Built in 3 Stop ND Filter
- Leaf Shutter

|           |                      |
|-----------|----------------------|
| X16321066 | X100S Black          |
| X16416445 | X100S Digital Camera |

**ARGRAPH**  
CORP

[www.argraph.com](http://www.argraph.com)

Address: 111 Asia Place, Carlstadt, NJ 07072  
Phone: 201.939.7722

Twitter: @argraph

# FUJIFILM

## X-SERIES DIGITAL CAMERAS

### XQ1



- 12.0MP 2/3" X-Trans CMOS II Sensor
- High speed EXR Processor II
- Intelligent Hybrid Auto Focus (High Speed Phase Detection + Contrast AF)
- Ultra-fast autofocus of 0.06sec.\*
- Bright Fujinon Optical 4x Power Zoom Lens F1.8-4.9 (25-100mm equiv.) w/ OIS
- Intelligent Digital Zoom to 16x
- Lens Modulation Optimizer technology
- Focus peaking
- High speed continuous shooting of 12fps at full resolution (max. 9 frames)
- Customizable Control Ring - up to 13 settings
- Bright, high contrast 3.0" (920,000 dot) LCD
- Full HD Movie @ 60fps (1920x1080) w/ Hybrid AF
- Compact, all metal body
- 8 Artistic filter modes + 3 film simulation modes
- One-touch wireless connectivity

X16410609 XQ1 Digital Camera (Black)  
X16410594 XQ1 Digital Camera (Silver)

### XQ2



- 12 Megapixels 2/3" X-Trans CMOS II
- EXR Processor II
- AF speed 0.06 seconds
- F1.8-F4.9 4x optical zoom equivalent to 25-100mm in 35mm format
- 4x Intelligent Digital Zoom (16X combined with optical zoom)
- 3" (920,000 dot) premium clear LCD (High contrast, High Brightness & Wide viewing angle)
- ISO100 – 12800
- Full HD Movie
- Wi-Fi enabled
- NEW 'Classic Chrome' and other film simulation

X16454813 XQ2 Digital Camera (Black)  
X16454942 XQ2 Digital Camera (Silver)  
X16455075 XQ2 Digital Camera (White)

### X30



- 2/3-inch X-Trans CMOS II with primary color filter
- Internal memory (approx. 55MB)
- Fujinon 4x optical zoom lens
- Intelligent digital zoom approx. 2x (up to 8x when combined with optical zoom)
- Intelligent Hybrid AF (TTL contrast AF / TTL phase detection AF), AF assist illuminator available
- NP-95 Li-ion battery (included)
- 0.39-in., approx. 2.360K-dot OLED color view finder

X16437695 X30 Digital Camera (Silver)  
X16437542 X30 Digital Camera (Black)

### X100T



- 12 Megapixels 2/3" X-Trans CMOS II
- EXR Processor II
- AF speed 0.06 seconds
- F1.8-F4.9 4x optical zoom equivalent to 25-100mm in 35mm format
- 4x Intelligent Digital Zoom (16X combined with optical zoom)

X16454813 XQ2 Digital Camera (Black)  
X16454942 XQ2 Digital Camera (Silver)  
X16455075 XQ2 Digital Camera (White)

**ARGRAPH**  
CORP

[www.argraph.com](http://www.argraph.com)

Address: 111 Asia Place, Carlstadt, NJ 07072  
Phone: 201.939.7722

Twitter: @argraph

# FUJIFILM

## X-SERIES

### FUJINON XF-LENSES

| LENS  | XF 10-24mmF4 R OIS   | XF56mmF1.2 R  |
|---|--|---|
| CONSTRUCTION                                      | 14 elements in 10 groups (includes 4 aspherical and 3 extra low dispersion elements) | 11 elements in 8 groups (includes 1 aspherical and 2 extra low dispersion elements)                   |
| FOCAL LENGTH (35MM FORMAT EQUIVALENT)             | f = 10-24mm<br>(15-36mm)   | f = 56mm<br>(85mm)  |
| ANGLE OF VIEW                                     | 110°-61.2°   | 28.5°   |
| MAX. APERTURE                                     | F4   | F1.2  |
| MIN. APERTURE                                     | F22  | F16   |
| APERTURE CONTROL<br>NUMBER OF BLADES<br>STOP SIZE | 7 (rounded diaphragm opening)<br>1/3 EV (16 stops)                                   | 7 (rounded diaphragm opening)<br>1/3 EV (23 STOPS)<br>*1/2 EV, from max. aperture to next step, only. |
| FOCUS RANGE                                       | Normal: 0.5m - ∞ Macro: 24cm - 3m  | Normal: 0.7m - ∞ Macro: 0.7 - 3m  |
| MAX. MAGNIFICATION                                | 0.16x (Telephoto)  | 0.09x   |
| EXTERNAL DIMENSIONS                               | ø 78mm x 87mm(Wide)/87mm (Telephoto)   | ø 73.2mm x 69.7mm   |
| WEIGHT (No caps or hoods)                         | 14.5oz   | 14.3oz  |
| FILTER SIZE                                       | ø 72mm   | ø 62mm  |



X16443072  
X16418649



XF10-24mmF4 R OIS (15-36mm)  
XF56mmF1.2 R (85mm)

# FUJIFILM

# X-SERIES

# FUJINON XF-LENSES

| LENS  | XF-18mm F2 R                                    | XF-35mm F1.4 R                                  | XF-60mm F2.4 R Macro  |
|---|---|---|---|
| CONSTRUCTION                                | 8 elements in 7 groups (inc. 2 asph. elements)  | 8 elements in 6 groups (inc. 1 asph. element)   | 10 elements in 8 groups (inc. 1 asph. element & 1 abnormal disp. elem.) |
| FOCAL LENGTH (35MM FORMAT EQUIVALENT)       | f = 18mm (27mm)                                 | f = 35mm (53mm)                                 | f = 60mm (91mm)   |
| ANGLE OF VIEW                               | 76.5°   | 44.2°   | 26.6°   |
| MAX. APERTURE                               | F2.0  | F1.4  | F2.4  |
| MIN. APERTURE                               | F16   | F16   | F22   |
| APERTURE CONTROL NUMBER OF BLADES STOP SIZE | 7 (rounded diaphragm opening) 1/3 EV (20 stops) | 7 (rounded diaphragm opening) 1/3 EV (22 stops) | 9 (rounded diaphragm opening) 1/3 EV (21 stops)                         |
| FOCUS RANGE                                 | Approx. 18mm - ∞                                | Approx. 28mm - ∞                                | Approx. 26.7mm - ∞  |
| MAX. MAGNIFICATION                          | 0.14x   | 0.17x   | .05x  |
| EXTERNAL DIMENSIONS                         | ø 64.5mm x 40.6mm                               | ø 65.0mm x 54.9mm                               | ø 64.1mm x 70.9mm   |
| WEIGHT (No caps or hoods)                   | Approx. 4.09oz                                  | Approx. 6.59oz                                  | Approx. 7.58oz  |
| FILTER SIZE                                 | ø 52mm  | ø 52mm  | ø 39mm  |



X16240743  
X16240755  
X16240767



XF18mm (27mm) F2.0  
XF35mm (53mm) F1.4  
XF60mm (90mm) F2.4



# FUJIFILM

## X-SERIES

### FUJINON XF-LENSES

| LENS  | XF-14mm F2.8 R  | XF-23mm F1.4 R  | XF-27mm F2.8 R Macro                                       |
|---|---|---|--|
| CONSTRUCTION                                | 10 elements in 7 groups<br>(inc. 2 asph. & 3 extra low dispersion elements) | 11 elements in 8 groups<br>(including 1 aspherical element) | 7 elements in 5 groups<br>(including 1 aspherical element) |
| FOCAL LENGTH (35MM FORMAT EQUIVALENT)       | f = 14mm<br>(21mm)  | f = 23mm<br>(35mm)  | f = 27mm<br>(41mm)   |
| ANGLE OF VIEW                               | 90.8°   | 63.4 °  | 55.5°  |
| MAX. APERTURE                               | F2.8  | F1.4  | F2.8   |
| MIN. APERTURE                               | F22   | F16   | F16  |
| APERTURE CONTROL NUMBER OF BLADES STOP SIZE | 7 (rounded diaphragm opening) 1/3 EV (19 stops)                             | 7 (rounded diaphragm opening) 1/3 EV (22 stops)             | 7 (rounded diaphragm opening) 1/3 EV (16 stops)            |
| FOCUS RANGE                                 | Approx. 18cm - ∞  | Normal: 0.6cm - ∞ Macro: 28cm - ∞                           | Approx. 0.6cm - ∞  |
| MAX. MAGNIFICATION                          | 0.12x   | 0.1x  | 0.1x   |
| EXTERNAL DIMENSIONS                         | ø 65.0mm x 58.4mm   | ø 72mm x 63mm   | ø 61.2mm x 23mm  |
| WEIGHT (No caps or hoods)                   | 8.29oz  | 10.58oz   | 2.75oz   |
| FILTER SIZE                                 | ø 58mm  | ø 62mm  | ø 39mm   |



X16276481  
X16405575  
X16389123  
X16401581



XF14mm (21mm) F2.8  
XF23mm (35mm) F1.4R  
XF27mm (41mm) F2.8 (Black)  
XF27mm (41mm) F2.8 (Silver)



# FUJIFILM

## X-SERIES

### FUJINON XF-LENSES

| LENS  | XF-18-55mm F2.8-4 OIS  | XF-55-200mm F3.5 - 4.8 OIS   |
|---|--|--|
| CONSTRUCTION                                | 14 elements in 10 groups (inc. 3 asph. element & 1 abnormal disp. element) | 14 elements in 10 groups (inc. 1 asph. element & 2 extra low disp. elements) |
| FOCAL LENGTH (35MM FORMAT EQUIVALENT)       | f = 18-55mm<br>(27.4mm-83.8mm)   | f = 55mm - 200mm<br>(82.5mm-300mm)   |
| ANGLE OF VIEW                               | 79.1°-28.4°  | 29.0°-8.1°   |
| MAX. APERTURE                               | F2.8-F4.0  | F3.5 - 4.8   |
| MIN. APERTURE                               | F22  | F22  |
| APERTURE CONTROL NUMBER OF BLADES STOP SIZE | 7 (rounded diaphragm opening)<br>1/3 EV (19 stops)                         | 7 (rounded diaphragm opening)<br>1/3 EV (17 stops)                           |
| FOCUS RANGE                                 | Wide Approx. 30cm - ∞ Tele Approx: 45cm - ∞                                | Normal approx. 1.1m - ∞  |
| MAX. MAGNIFICATION                          | 0.08-0.15x   | .18x (Telephoto)   |
| EXTERNAL DIMENSIONS                         | ø 65.0mm x 70.4mm (Wide) /97.9mm (Tele)                                    | ø 75.0mm x 118mm (Wide) /177mm (Tele)  |
| WEIGHT (No caps or hoods)                   | Approx. 11.64oz  | Approx. 20.46oz  |
| FILTER SIZE                                 | ø 58mm   | ø 62mm   |



X16276479 XF 18-55mm (27.4 ~ 83.8mm) F2.8 - 4.0  
 X16384941 XF 55-200mm (82.5 ~ 300 mm) F3.5 - 4.8

# FUJIFILM

## X-SERIES

### FUJINON XC-LENSES

| LENS  | XC-16-50mm F3.5-5.6   | XC-50-230mm F4.5 - 6.7 OIS  |
|---|---|---|
| CONSTRUCTION                                      | 12 elements in 10 groups (including 3 aspherical element & 1 extra low disp.) | 13 elements in 10 groups (inc. 1 asph. element & 1 extra low disp. element) |
| FOCAL LENGTH (35MM FORMAT EQUIVALENT)             | f = 16-50mm (24-76mm)   | f = 50mm - 230mm (76mm-350mm)   |
| ANGLE OF VIEW                                     | 83.2 °- 31.7 °  | 31.7°-7.1°  |
| MAX. APERTURE                                     | F3.5-5.6  | F4.5 - 6.7  |
| MIN. APERTURE                                     | F22   | F22   |
| APERTURE CONTROL<br>NUMBER OF BLADES<br>STOP SIZE | 7 (rounded diaphragm opening)<br>1/3 EV (17 stops)                            | 7 (rounded diaphragm opening)<br>1/3 EV (15 stops)                          |
| FOCUS RANGE                                       | Approx. 0.6cm - ∞   | Normal approx. 1.1m - ∞   |
| MAX. MAGNIFICATION                                | 0.15x (Telephoto)   | 0.2x (Telephoto)  |
| EXTERNAL DIMENSIONS                               | ø 62.6mm x 65.2mm (Wide) /93.8mm (Tele)                                       | ø 69.5mm x 111mm (Wide)/177mm (Tele)  |
| WEIGHT (No caps or hoods)                         | 6.87oz  | Approx. 13.23oz   |
| FILTER SIZE                                       | ø 58mm  | ø 58mm  |

\* XC 16-50mm lens not available for individual sale. Available only in X-M1 and X-A1 Zoom Kits



X16405604  
X16405628  
X16401608  
X16401608

XC 50-230mm (76 ~ 350mm) F4.5 - 6.7 (Black)  
XC 50-230mm (76 ~ 350mm) F4.5 - 6.7 (Silver)  
XF 16-50mm (27 ~ 76mm) F3.5 - 5.6 (Silver)  
XF 16-50mm (27 ~ 76mm) F3.5 - 5.6 (Black)



# FUJIFILM X-SERIES

## WCL-X100

Description: Converts X100 and X100s Cameras to 28mm focal length. Mag ~ x0.8, Filter size: 49mm



## M-Mount Adapter (X-Pro1)

Description: SS and Aluminum, Adapter allows use of M Mount lenses on X-Pro1, compatible with Hybrid Multi-viewfinder, 27.8mm distance to sensor, lens profiles and corrections available (firmware version 1.10 or later).



MCEX-11



MCEX-16

X16260298  
X16260327  
X16267038  
X16451720  
X16451744

WCL-X100S X100 Wide Conversion Lens (Silver)  
WCL-X100B X100 Wide Conversion Lens (Black)  
X-Pro1 M-MOUNT Adapter  
Fuji Macro Extension Tube MCEX- 11  
Fuji Macro Extension Tube MCEX- 16